



## SLOAN VALVE – WATER & ENERGY EFFICIENCY STATISTICS

**\*\* The following products will be displayed at Sloan Valve's booth at Greenbuild. Below are each products water and energy efficiency statistics:**

**1. Sloan Waterfree Urinal**

Energy Policy Act (EPA) Requirements: 1.0 gallons per flush (gpf)  
Sloan Performance: 0.0 gpf  
**Sloan Savings: 100%**

**2. Sloan 1 Pint Urinal System (SMOOTH AC-Powered Flushometer)**

EPA Requirements: 1.0 gpf  
Sloan Performance: 1/8 gpf  
**Sloan Savings: 88%**

**3. Sloan ECOS™ Dual-Flush Flushometer (Battery Powered Water Closet Flushometer)**

EPA Requirements: 1.6 gpf  
Sloan Performance: 1.6 gpf  
Dual-Flush: 1.1 gpf  
**Sloan Savings 21%**

**4. SOLIS™ Dual-Flush Flushometer (Solar Powered Water Closet Flushometer)**

EPA Requirements: 1.6 gpf  
Sloan Performance: 1.6 gpf  
Dual Flush: 1.1 gpf  
**Sloan Savings: 21%**

**5. Sloan 1 Pint Urinal System (SOLIS™ Solar-Powered Flushometer)**

EPA Requirements: 1.0 gpf  
Sloan Performance: 1/8 gpf  
**Sloan Savings: 88%**

**6. Sloan ECOS™ Dual-Flush Flushometer (Battery Powered Water Closet Flushometer)**

EPA Requirements: 1.6 gpf  
Sloan Performance: 1.28 gpf  
Dual-Flush: 0.8 gpf  
**Sloan Savings 40%**

**7. UPPERCUT™ Dual-Flush Flushometer (Manual Water Closet Flushometer)**

EPA Requirements: 1.6 gpf  
Sloan Performance: 1.6 gpf (down)  
Dual-Flush: 1.1 gpf (up)  
**Sloan Savings: 21%**

**8. HEU Urinal System (Sloan Royal® Flushometer)**

EPAct Requirements: 1.0 gpf  
Sloan Performance: ¼ gpf  
**Sloan Savings: 75%**

**9. Sloan 1 Pint Urinal System (SMOOTH Battery-Powered Flushometer)**

EPAct Requirements: 1.0 gpf  
Sloan Performance: 1/8 gpf  
**Sloan Savings: 88%**

**10. SOLIS™ Solar-Powered Faucet**

EPAct Requirements: 2.5 gallons per minute (gpm)  
Sloan Performance 0.5 gpm  
**Sloan Savings: 80%**

**11. Act-O-Matic® Low Consumption Showerhead**

EPAct Requirements: 2.5 gpm  
Sloan Performance: 2.0 gpm  
**Sloan Savings: 20%**

**12. FLUSHMATE® IV**

EPAct Requirements: 1.6 gpf  
Sloan Performance: 1.0 gpf  
**Sloan Savings: 38%**

**13. SloanStone® ELS Series (SOLIS™ Faucet)**

EPAct Requirements: 2.5 gpm  
Sloan Performance: 0.5 gpm  
**Sloan Savings: 80%**

**14. XEerator® Hand Dryer**

Dries hands in 10-15 seconds  
**Sloan Savings: 80%**

###